

# 10228094 ALTUMA MXB 50-CCL ETDD 1CH


GalliSpec LED luminaire for animal farming

made by...



|  |  |
|--|--|
| <b>Dimension / Weight</b>                    | 1.340 x 112 x 122 mm / 4.2 kg  |
| <b>Luminous Flux / Light color / CRI</b>     | 5.000 lm / GalliSpec / 80  |
| <b>Maximum electrical load / typical</b>     | 45 / < 45  |
| <b>Rated voltage / frequency</b>             | 220-240 V / 0..50-60 Hz  |
| <b>Protection class</b>                      | Class 1  |
| <b>Protection rating / impact resistance</b> | IP69K / IK10   |
| <b>Chemical resistance</b>                   | See appendix   |
| <b>Life span / max ambient temperatures</b>  | L80 (25°C) 100.000 h / -35..+35° C   |
| <b>Fire protection</b>                       | GRP and PMMA: Flammability (UL94): HB, Glow wire test (EN 60695-2-11): 650°C |
| <b>Control gear</b>                          | Electronic transformer - 1 channel, digitally dimmable (DALI DT6)            |
| <b>Connection method</b>                     | Open cable   |
| <b>Color of housing / endcaps</b>            | Light grey / red (other colors available upon request)                       |
| <b>Accessories</b>                           | Stainless steel fixing brackets included; pipe clamps optional               |

### Light distribution



Maximum wide beam optic style. Uniform light up to 14 m wide at 3 m installation height.

### Approvals

