

# 10228095 ALTUMA MXB 30-CCL ETDD 2x2CH TWW


GalliSpec LED luminaire for animal farming

made by...



<b>Dimension / Weight</b>	1.340 x 112 x 122 mm / 4.2 kg
<b>Luminous Flux / Light color / CRI</b>	5.000 lm / GalliSpec / 80
<b>Maximum electrical load / typical</b>	45 / < 45
<b>Rated voltage / frequency</b>	220-240 V / 0..50-60 Hz
<b>Protection class</b>	Class 1
<b>Protection rating / impact resistance</b>	IP69K / IK10
<b>Chemical resistance</b>	See appendix
<b>Life span / max ambient temperatures</b>	L80 (25°C) 100.000 h / -35..+35° C
<b>Fire protection</b>	GRP and PMMA: Flammability (UL94): HB, Glow wire test (EN 60695-2-11): 650°C
<b>Control gear</b>	Electronic transformer - 1 channel, digitally dimmable (DALI DT6)
<b>Connection method</b>	3m cable (NYY 1.5 mm <sup>2</sup> ) with Wieland connector (TWW)
<b>Color of housing / endcaps</b>	Light grey / red (other colors available upon request)
<b>Accessories</b>	Stainless steel fixing brackets included; pipe clamps optional

**Light distribution**



Maximum wide beam optic style. Uniform light up to 14 m wide at 3 m installation height.

**Approvals**

