

# 10228096 ALTUMA MXB 60-750 ETDD G2B PisciLux®

LED luminaire for animal farming




made by...



<b>Dimension / Weight</b>	1.340 x 112 x 122 mm / 4.2 kg
<b>Luminous Flux / Light color / CRI</b>	6.000 lm / PisciLux / 70
<b>Maximum electrical load / typical</b>	44 / < 44
<b>Rated voltage / frequency</b>	220-240 V / 0..50-60 Hz
<b>Protection class</b>	Class 1
<b>Protection rating / impact resistance</b>	IP69K / IK10
<b>Chemical resistance</b>	See appendix
<b>Life span / max ambient temperatures</b>	L80 (25°C) 100.000 h / -35..+35° C
<b>Fire protection</b>	GRP and PMMA: Flammability (UL94): HB, Glow wire test (EN 60695-2-11): 650°C
<b>Control gear</b>	Electronic transformer - 2 channel, digitally dimmable (DALI DT6)
<b>Connection method</b>	Open cable, 3m NYY 1.5 mm <sup>2</sup>
<b>Color of housing / endcaps</b>	Light grey / red (other colors available upon request)
<b>Accessories</b>	Stainless steel fixing brackets included; pipe clamps optional

### Light distribution



Maximum wide beam optic style. Uniform light up to 14 m wide at 3 m installation height.

### Approvals

