

10228121 ALTUMA 0.7 MXB 28-CCL ETDD 1CH


GalliSpec LED luminaire for animal farming

made by...



| | |
|--|--|
| Dimension / Weight | 787 x 112 x 122 mm / 4.2 kg |
| Luminous Flux / Light color / CRI | 2.800 lm / GalliSpec / 80 |
| Maximum electrical load / typical | 26 / < 26 |
| Rated voltage / frequency | 220-240 V / 0..50-60 Hz |
| Protection class | Class 1 |
| Protection rating / impact resistance | IP69K / IK10 |
| Chemical resistance | See appendix |
| Life span / max ambient temperatures | L80 (25°C) 100.000 h / -35..+35° C |
| Fire protection | GRP and PMMA: Flammability (UL94): HB, Glow wire test (EN 60695-2-11): 650°C |
| Control gear | Electronic transformer - 1 channel, digitally dimmable (DALI DT6) |
| Connection method | 3 m NYY 1.5 mm ² open cable |
| Color of housing / endcaps | Light grey / red (other colors available upon request) |
| Accessories | Stainless steel fixing brackets included; pipe clamps optional |

Light distribution



Maximum wide beam optic style. Uniform light up to 14 m wide at 3 m installation height.

Approvals

